

54HL4R-B 425-445 Watt

Mechanical Characteristics

| | |
|------------------|--|
| Cell Type | N -type Mono-crystalline |
| No. of cells | 108 (54×2) |
| Dimensions | 1762×1134×30mm |
| Weight | 21.0 kg |
| Front Glass | 3.2 mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass |
| Frame | Anodized Aluminium Alloy |
| Junction Box | IP68 Rated |
| Protection Class | Class II |
| IEC Fire Type | Class C |
| Output Cables | 4.0 mm ² (+): 400 mm , (-): 200 mm or Customized Length |

Packaging Configuration

| | |
|---|---|
| Pallet Dimensions | 1792×1120×1249 mm |
| Packing Detail (Two pallets = One stack) | 36 pcs/pallets, 72 pcs/stack, 936 pcs/ 40'HQ Container |

Specifications (STC)

| | | | | | |
|----------------------------------|------------|-------|-------|-------|-------|
| Maximum Power - Pmax [Wp] | 425 | 430 | 435 | 440 | 445 |
| Maximum Power Voltage - Vmp [V] | 32.37 | 32.58 | 32.78 | 32.99 | 33.19 |
| Maximum Power Current - Imp [A] | 13.13 | 13.20 | 13.27 | 13.34 | 13.41 |
| Open-circuit Voltage - Voc [V] | 38.95 | 39.16 | 39.36 | 39.57 | 39.77 |
| Short-circuit Current - Isc [A] | 13.58 | 13.65 | 13.72 | 13.80 | 13.87 |
| Module Efficiency STC [%] | 21.27 | 21.52 | 21.77 | 22.02 | 22.27 |
| Power Tolerance | 0 ~ + 3 % | | | | |
| Temperature Coefficients of Pmax | -0.29 %/°C | | | | |
| Temperature Coefficients of Voc | -0.25 %/°C | | | | |
| Temperature Coefficients of Isc | 0.045 %/°C | | | | |

STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5

Specifications (NOCT)


| | | | | | |
|---------------------------------|-------|-------|-------|-------|-------|
| Maximum Power - Pmax [Wp] | 320 | 323 | 327 | 331 | 335 |
| Maximum Power Voltage - Vmp [V] | 30.19 | 30.30 | 30.50 | 30.73 | 30.93 |
| Maximum Power Current - Imp [A] | 10.60 | 10.66 | 10.72 | 10.77 | 10.83 |
| Open-circuit Voltage - Voc [V] | 37.00 | 37.20 | 37.39 | 37.59 | 37.78 |
| Short-circuit Current - Isc [A] | 10.96 | 11.02 | 11.08 | 11.14 | 11.20 |

NOCT: Irradiance 800W/m², Ambient Temperature 20°C, AM=1.5, Wind Speed 1m/s

Application Conditions

| | |
|---|---------------------|
| Operating Temperature | -40 °C ~ +85 °C |
| Maximum System Voltage | 1000/1500 VDC (IEC) |
| Maximum Series Fuse Rating | 25 A |
| Nominal Operating Cell Temperature - NOCT | 45 ± 2 °C |


Engineering Drawings



Note: For specific dimensions and tolerance ranges, please refer to the corresponding detailed module drawings.

Electrical Performance

Power-Voltage Curves (54HL4R-B 430W)



Current-Voltage Curves (54HL4R-B 430W)

